



TAJNOTENT

INSTRUCTIONS FOR FITMENT



*This fitment applies to a Corsa
2004-2011 tie on tonneau kit*

*Part NO:
CKDV04PL*

Thank you for choosing our product. Please adhere to these instructions as closely as possible. Always ensure all safety equipment is used and that a safe working environment is established.

TOOLS:

Electric Drill, 4.5mm steel drill bit, extension cord, pop-rivet gun, tape measure, pencil, all appropriate safety equipment and all parts provided in the tonneau kit.

Note: After any holes are drilled apply rust inhibitor (provided) before any screws or rivets are fastened

1. Before commencing fitment, check the contents of the kit and ensure it is the correct cover for your bakkie by laying it over the load-body and ensuring it fits correctly.
2. To attach aluminium rail, first pull off plastic liner on inside the cab behind the seats, in order to insert washers on rivets. Drill 4 holes in the centre of the indentations to ensure washers can be placed on the rivets.
3. Pull cover towards back. You will see two strips sewn across the cover. The support braces go across the load box in the centre of these strips. Mark centre points and fit bow clips flush with top edge of load box.
4. Insert longer support brace towards window and shorter towards tail gate.
5. Pull cover to back over tail gate. Turn up hem and mark centres of 3 cut outs along tailgate (2CM below plastic liner) and one on either back corner between loops, stitched on underside (3CM below plastic liner). Drill and pop rivet bobbins.
6. At the front fit one saddle hook on either side behind door to tie off ends of shock cord.
7. Once fitted the cover should fit tight and secure. Check that the elastic is pulled tight and that the support brace is inserted and working correctly.

Only use a mild soap when cleaning your cover.

Thank you for your purchase, we hope it meets your requirements adequately.

