



TAUNOTENT

FITMENT INSTRUCTIONS



TONNEAU COVER

These fitment instructions apply to:
FORD Ranger: Double Cab

Clip-on Kit to fit with
and without
Roll bar

Thank you for choosing our product. Please adhere to these instructions as closely as possible. Always ensure all safety equipment is used and that a safe working environment is established.

TOOLS: Tools required: Electric drill;
10mm Drill bit; screwdriver.

KIT COMPRISES:

- 1x Tonneau cover
- 2x Support braces
- 4x Support clips
- 4x G-clamps with hand screws
- 1x Front rail
- 3x Rivet nuts with 3x screws
- 2x Side rails with plastic end caps
- 1x Back rail
- 2x Plastic back corners with 4x turning screws

INSTRUCTIONS FOR FITMENT

1) Put the aluminum slide in rail on the top edge of the load body, beneath the window. The shorter lip of the rail to be positioned towards the cab. Mark and drill 3 holes according to rail. Insert rivet nuts into holes and then using screws, attach rail to edge.



2) Fasten the two side rails using 2x clamps per rail. The plastic caps must sit flush with the front outside edge of the aluminum rail which just has been attached. See Picture.



3) Install the rear rail over the tail gate by pushing the ends of the plastic corners into the open ends of the side rails. Fasten into place by turning screws as tightly as possible



4) Insert support braces into bow clips ensuring they are equally spaced along the length of the load box. Slide cover into front rail and close velcro around roll-bar and then pull cover towards tailgate.





TAUNOTENT

FITMENT INSTRUCTIONS



TONNEAU
COVER

These fitment instructions apply to:
FORD Ranger: Double Cab

Clip-on Kit to fit with
and without
Roll bar

Thank you for choosing our product. Please adhere to these instructions as closely as possible. Always ensure all safety equipment is used and that a safe working environment is established.

INSTRUCTIONS FOR FITMENT *CONTINUED*

6) Line up all the chips at tailgate first and then push them all down at once so that they clip into the rail. Do the same on the two sides. Pull the corners using the tabs. When removing the cover start by lifting up the tabs to loosen the chips



- 7) The tailgate can open and close with the cover fitted.
- 8) The cover can be rolled to the front and fastened using the straps.
- 9) Should any part of the kit be lost or broken they can be purchased separately .



Retighten clamps and hand screws regularly as they tend to open while traveling

Should you experience any problems in fitting please do not hesitate to call us on 0861 82 8668