



TAUNOTENT

# FITMENT INSTRUCTIONS



These fitment instructions apply to:  
FORD RANGER/MAZDA BT50: Double Cab/Extended cab/LWB with Giflo Roll Bar

Clip-on Kit to fit with Giflo Roll Bar

Thank you for choosing our product. Please adhere to these instructions as closely as possible. Always ensure all safety equipment is used and that a safe working environment is established.

### TOOLS:

Tools required: screwdriver.

### KIT COMPRISES:

- 1x Tonneau cover
- 2x Support braces
- 8x Bow Clips
- 8x G-clamps with hand screws
- 1x Front rail
- 4x Side rails with plastic end caps
- 1x Back rail
- 2x Plastic back corners with
- 4x turning screws

## INSTRUCTIONS FOR FITMENT

1) Put the aluminum slide -in rail on the top edge of the load body, beneath the window (if rubberized mark 2 pencil marks on the rubberizing with the use of the aluminum slide on rail . The shorter lip of the rail to be positioned towards the cab, attach rail using screws.



2) Fasten the four side rails (the 2 shorter rails are to be placed and fitted between the roll bar, and the two longer rails fitted behind the end of the roll bar) using 2x clamps per rail (8 clamps in total). See Picture.



3) Install the rear rail over the tail gate by pushing the ends of the plastic corners into the open ends of the side rails. Fasten into place by turning screws as tightly as possible



4) Insert support braces into bow clips (Double cab and extended cab) the longer support brace fitted in the bow clips closest to the back window of the vehicle and the shorter one fitted in the bow clips closest to the tail gate ensuring they are equally spaced along the length of the load box. Slide cover into front rail and close velcro around roll-bar and then pull cover towards tailgate. The LWB has 3 support braces the longest one placed first closest to the window, the second longest placed next and the shortest one placed last near the tailgate.





TAUNOTENT

## FITMENT INSTRUCTIONS



TONNEAU  
COVER

These fitment instructions apply to:  
FORD RANGER/MAZDA BT50: Double  
Cab/Extended cab/LWB with Giflo Roll Bar

Clip-on Kit to fit with  
Giflo Roll Bar

Thank you for choosing our product. Please adhere to these instructions as closely as possible. Always ensure all safety equipment is used and that a safe working environment is established.

### INSTRUCTIONS FOR FITMENT *CONTINUED*

6) Line up all the chips at tailgate first and then push them all down at once so that they clip into the rail. Do the same on the two sides. Pull the corners using the tabs. When removing the cover start by lifting up the tabs to loosen the chips



7) The tailgate can open and close with the cover fitted.

8) The cover can be rolled to the front and fastened using the straps.

9) Should any part of the kit be lost or broken they can be purchased separately .



**Retighten clamps and hand screws regularly as they tend to open while traveling**

**Should you experience any problems in fitting please do not hesitate to call us on 0861 82 8668**