

FITMENT INSTRUCTIONS



TONNEAU COVER

FITMENT INSTRUCTIONS FOR A
DOUBLE CAB PLAIN WITHOUT
ROLLBAR

NEXT GEN RANGER 2023

KIT CONSIST OF THE FOLLOWING:

- X1 FRONT RAIL
- X1 TAILGATE RAIL
- X2 SIDE RAILS (RIGHT AND LEFT)
- X2 SUPPORT BRACES (BACK AND FRONT)
- X2 CORNERS
- X4 CORNER SCREWS
- X4 CLAMPS
- X2 6MM BOLTS
- X2 6MM WASHERS
- X2 6MM NUTS
- X2 8MM BOLTS
- X2 8MM WASHERS
- TONNEAU COVER

YOU WILL NEED:

- 2X 10 SPANNER / SOCKET WRENCH
- 13 SPANNER / SOCKET WRENCH

1. FITTING THE FRONT RAIL



LINE UP THE HOLES ON THE FRONT RAIL WITH THE HOLES ON THE FRONT EDGE OF THE LOADBIN.



TIGHTEN BOTH BOLTS USING 13 SPANNER / SOCKET WRENCH.

2. FITTING THE LEFT AND RIGHT-SIDE RAILS



FIT THE LEFT AND RIGHT-SIDE RAILS .



LINE UP STOPPER BRACKETS WITH THE HOLE IN THE FRONT RAIL. TIGHTEN STOPPER BRACKET TO THE FRONT RAIL USING THE 2X 6mm BOLTS PROVIDED. TIGHTEN WITH A 2X 10 SPANNER / SOCKET WRENCH (ONE TO HOLD AND ONE TO TURN). DO THE SAME ON THE OPPOSITE SIDE.

3. FITTING THE BACK CORNERS AND TAILGATE RAIL



FIT THE LEFT AND RIGHT CORNER INTO THE TAILGATE RAIL USING THE SCREWS PROVIDED.



PUSH TAILGATE RAIL INTO SIDE RAILS AND TIGHTEN WITH SCREWS.



TAUNOTENT

+27 (0)11 455 0627 / +27 (0)11 026 4790 / +27 (0)63 517 0195
Unit 3, 159 Greenvale Road, Wilbart, Gauteng 1610

www.taunotent.co.za
info@taunotent.co.za

FITMENT INSTRUCTIONS

4. FITTING CLAMPS



FULLY LOOSEN ALL 4 CLAMP SCREWS.



INSERT ALL CLAMPS INTO HOLES INSIDE RAIL AND TIGHTEN JUST SO THAT SIDE RAILS CAN STILL BE MANEUVERED.

5. LINING UP RAILS



USE THE TAUNOTENT GAUGE PROVIDED TO LINE UP THE RAILS TO THE OUTSIDE OF THE BODY OF THE VEHICLE. THIS MUST ONLY BE DONE TOWARDS THE FRONT AND THE BACK OF THE VEHICLE, NOT IN THE CENTRE.

*DO NOT THROW YOUR GAUGE AWAY AS YOU WILL NEED IT EVERY TIME YOU NEED TO REFIT YOUR COVER. SOMETIMES THE CLAMPS COME LOOSE AND YOU WILL NEED YOUR GAUGE TO REFIT THE RAILS.



ONCE ALL IS LINED UP AND IN PLACE, TIGHTEN ALL THE CLAMPS TO ENSURE THE RAILS ARE NOT MOVING OR SLIDING.

*PLEASE TIGHTEN YOUR CLAMPS AT LEAST ONCE A MONTH AS THEY BECOME LOOSE DURING TRAVELLING.

6. FITTING THE SUPPORT BRACES



USE THE SUPPORT BRACES LABELED FRONT AND BACK AND SLOT THEM INTO THE FOUR BOWCLIPS.

7. COVER



SLIDE THE COVER INTO THE FRONT RAIL AND PULL TOWARDS THE TAILGATE.



TAUNOTENT

+27 (0)11 455 0627 / +27 (0)11 026 4790 / +27 (0)63 517 0195
Unit 3, 159 Greenvale Road, Wilbart, Gauteng 1610

www.taunotent.co.za
info@taunotent.co.za

FITMENT INSTRUCTIONS

8. CLIPPING THE CHIPS



STARTING AT THE TAILGATE IN THE CENTRE, LINE UP THE CHIPS WITH THE LIP OF THE TAILGATE RAIL AND BEGIN PRESSING THE CLIPS INTO THE RAIL. CONTINUE CLIPPING THE CHIPS INTO THE RAILS UNTIL THE COVER IS SECURELY FITTED.



TROUBLESHOOTING:

If the cover is too tight or too loose when clipping into the rails, then rails need to be adjusted accordingly. Please feel free to call us if you have any fitment issues.

NOTE:

*DO NOT THROW YOUR GAUGE AWAY AS YOU WILL NEED IT EVERY TIME YOU NEED TO REFIT YOUR COVER. SOMETIMES THE CLAMPS COME LOOSE AND YOU WILL NEED YOUR GAUGE TO REFIT THE RAILS. CAN BE USED AS A KEY RING.

*PLEASE TIGHTEN YOUR CLAMPS AT LEAST ONCE A MONTH AS THEY BECOME LOOSE DURING TRAVELLING.

WE THANK YOU FOR PURCHASING A TAUNOTENT PRODUCT

Warranty: The stitching is guaranteed for 6 months. Please only use Sunlight dish soap to wash the cover and Dubbin to polish. All car wash products and polishes should not be used on the tonneau cover, as well as, high pressure hoses and brushes.



TAUNOTENT

+27 (0)11 455 0627 / +27 (0)11 026 4790 / +27 (0)63 517 0195
Unit 3, 159 Greenvale Road, Wilbart, Gauteng 1610

www.taunotent.co.za
info@taunotent.co.za